



TRUSTED PROTECTION®
INSIDE AND OUT

TECHNICAL DATA SHEET

QUASAR® X7+ EXTENDED CUFF NITRILE EXAM GLOVES

PRODUCT DESCRIPTION

PRODUCT:	Quasar® X7+		
GRADE:	Exam		
MATERIAL:	Nitrile	POWDER: Powder-Free	
THICKNESS:	Finger: 5.6mil / 0.14mm	Palm: 5.1mil / 0.13mm	Cuff: 4.6mil / 0.12mm
COLOR:	Hi-Viz Orange		
SURFACE:	Fully Textured		
LENGTH:	10.5" / 267mm	WEIGHT: 8.0g	
FIT TYPE:	Ambidextrous		
CUFF TYPE:	Beaded		
WATERTIGHT AQL:	0.65		
ORIGIN COUNTRY:	China		

PHYSICAL PROPERTIES

	BEFORE AGING	AFTER AGING	ASTM METHOD
TENSILE STRENGTH:	22 MPa	20 MPa	D412-10
ELONGATION:	570%	550%	D412-10

ORDERING

	XS	S	M	L	XL	XXL
SIZE:	5.5 - 6.0	6.5 - 7.0	7.5 - 8.0	8.5 - 9.0	9.5 - 10	10.5 - 11.0
AVG. PALM WIDTH:	2.9"/73mm	3.5"/88mm	3.8"/98mm	4.3"/108mm	4.7"/118mm	5.0"/127mm
PART NUMBER:	N017751	N017752	N017753	N017754	N017755	N017756
PACKAGING:	100 gloves per box, 10 boxes per case					

INTEGRATED TECHNOLOGY



- **MilTek™** offers durability and tactile sensitivity.
- **TouchTek™** protects skin and prevents contamination.
- Extended Cuff provides added protection.

PERFORMANCE STANDARDS

EN374-1:2003



EN374-2



LEVEL 2

REGULATORY COMPLIANCE

EN 420: 2003
EN 455: 2000-2015
ASTM F1671-97
ASTM F739-12
REACH EU 1907/2006
DIRECTIVE 2011/65/EU
EU Reg 528/2012
CAT III COMPLEX DESIGN
FDA 21 CFR 177.2600
Component materials comply with
FDA regulations for food contact

CE
EN455

CE 0493

EAC
TP TC 019/2011

EAC

RECOMMENDED APPLICATIONS

- Assembly
- Maintenance
- Fabrication
- Painting
- Cleaning
- Chemical
- Liquid Handling
- Oily or Wet Surfaces
- Laboratory
- Clinical

STORAGE

Keep out of sunlight. Store in a cool, dry place.
Keep away from sources of ozone or ignition.

